



Features

- Seven models
- 36" to 84" working widths
- Hydraulic drives are protected and isolated to provide maximum performance and reliability
- Delivers up to 9,370 lbs or dynamic force when operating at 20 GPM
- 15° oscillation of drums
- Steel drum has an adjustable steel scrap blade between the frame and the drum ensuring smooth and uniform compaction performance
- Ideal for rental fleets, contractors, landscaping, roadways, walkways, bike paths, golf courses bridges and parking lots

The **Bradco® Vibratory Roller** by Paladin, is skid steer compatible. The rollers are designed to follow ground contours for even compaction.



SPECIFICATIONS -SMOOTH DRUM	36"	48"	66"	73"	84"
Order Codes	109100 or 109101	10561	105062	105063	105064
A. Overall Width	42"	61"	72"	79"	90"
B. Drum Width	36"	48"	66"	73"	84"
C. Overall Height	22"	31"	31"	31"	31"
D. Overall Length	34"	39"	39"	39"	39"
E. Drum Diameter	20"	24"	24"	24"	24"
Operating Weight	840 lbs	1,680 lbs	2,150 lbs	2,300 lbs	2,530 lbs
Dynamic Force	2,488 lbs	5,750 lbs	7,800 lbs	8,550 lbs	9,370 lbs
Vibrating Speed (vpm)	2,000	2,600	2,600	2,600	2,600
Vibrating Weight	507 lbs	935 lbs	1,190 lbs	1,290 lbs	1,440 lbs
Drum Oscillation/Tile	15°	15°	15°	15°	15°
Hydraulic Motor Flow (gpm)	6-9 or 10-14	25	25	25	25

SPECIFICATIONS -PADDED DRUM	48"	66"	73"	84"
Order Codes	105065	105066	105067	105068
A. Overall Width	61"	72"	79"	90"
B. Drum Width	48"	66"	73"	84"
C. Overall Height	31"	31"	31"	31"
D. Overall Length	39"	39"	39"	39"
E. Drum Diameter (without pads)	20"	24"	24"	24"
Operating Weight	1,630 lbs	2,085 lbs	2,230 lbs	2,455 lbs
Dynamic Force	5,750 lbs	7,800 lbs	8,550 lbs	9,370 lbs
Vibrating Speed (vpm)	2,600	2,600	2,600	2,600
Vibrating Weight	507 lbs	935 lbs	1,190 lbs	1,290 lbs
Drum Oscillation/Tile	15°	15°	15°	15°
Maximum Flow	25	25	25	25

