



Features

- Available in 84" and 96"
- Hydro-electric controlled angle and tilt, using only one loader valve
- Angle 30° right or left off center
- Tilt 10° off horizontal both directions
- Tilt indicator visible from operator's seat
- Angle and tilt cylinders are interchangeable and equipped with self-aligning bushings
- Reversible ¾" x 8" bolt-on cutting edge & formed moldboard .31" thick & 28" high
- Large 3" center pivot pin with hardened steel bushings

The **Bradco® Dozer Blade** by Paladin with tilt attach, tilts the dozer blade for more precise grading, leveling and trenching. This means you get to the next job quicker!



| SPECIFICATIONS | 84" | 96" |
|---|-----|-----|
| Width from center line to inside edge at 15° | 44" | 50" |
| Width from center line to inside edge at 30° | 43" | 48" |
| Width at 15° angle | 82" | 93" |
| Width at 30° angle | 74" | 84" |
| Width from center line to outside edge at 15° angle | 38" | 44" |
| Width (overall) | 84" | 96" |
| Angle Left and Right | 30° | 30° |
| Tilt | 10° | 10° |
| Length (overall) | 37" | 37" |
| Height (overall) | 30" | 30" |

Additional Features

- Full length high carbon steel, replaceable skid shoe
- Set up to default in either tilt or angle position
- Universal skid-steer loader quick attach mounting, or use on skid-steers up to 110 HP

