



TECHNICAL SPECIFICATIONS AND STANDARD EQUIPMENT

- maximum horsepower: 260 HP (192 KW)
- PTO: 2-speed gearbox for 1000 rpm
No. of teeth: 17-22 = 357 rpm; 18-21 = 396 rpm
- 3-point hitch cat.3
- swinging front hitches
- roller adjustment with pins
- rear leveling bar adjustment with threaded bar
- tines 120x15x300 mm: working depth, approximately 30 cm
- mobile side plates
- side drive shafts with automatic safety device
- central drive shaft
- rear lights for road transport
- removable safety devices

ENERGY P									
	cm	cm	HP / KW	Kg	Kg	Kg	Kg	No.	
400	400	247	140/103	2,240	2,340	2,500	2,360	32	Central drive shaft S.10 L=835 tractor side 1"3/8 Z=6
500	500	247	160/118	2,470	2,600	2,800	2,620	40	
600	600	247	180/132	2,700	2,860	3,100	2,880	48	

ENERGY P	cage rollers		spikes rollers		packer rollers		spiral rollers	
400	500		560		555		470	
500								
600								

OPTIONAL ACCESSORIES:

Oil cooling kit for side gearboxes	
Oil cooling kit for central gearbox	
3-point hitch cat. 2 (supplied at a later time)	
Rear rollers - see page 209	
Counterplate for tine locking (rotor kit)	
Counterplate for tine locking (rotor kit) (supplied at a later time)	
Quick release rotor stone protector kit	
Stone protectors kit for quick release system rotor (supplied at a later time)	
Floating system kit	
Central track eraser tool	
Front track eraser	
Quick tine fitting kit (only at origin)	
Hydraulic kit for roller adjustment	