

## GRADING SCRAPERS



## **GSI SERIES**

## **FEATURES:**

- Heavy 5" x 5" steel tubing with 1/4" wall main front beam
- 3" x 3" steel tubing near support beam
- Two 1/2" x 6" heat treated reversible beveled cutting edges
- Easy to adjust cutting edges with settings of 0 to 1-1/2" below side panels (preset at 1/2")
- Front cutting blade is designed to adjust lower than the rear blade to compensate for additional wear
- 20" spacing between cutting edges to produce maximum mixing action when rebuilding gravel roads
- 1/4" x 18" x 60" formed side panels capture and retain material
- 3/8" x 2-1/2" replaceable skid plates on side panels

MODELS	WORKING WIDTH	SIDE PLATES	HITCH	CUTTING EDGES	REPLACEABLE SKIDS	DEPTH ADJUSTMENT	HP REQUIRED	NO. SHANKS	WEIGHT
GSI-7	84"	1/4" x 18" x 60"	Cat. 1 & 2	1/2" x 6"	3/8" x 2-1/2"	0 to 1-1/2"	45	7	935
GSI-8	96"	1/4" x 18" x 60"	Cat. 1 & 2	1/2" x 6"	3/8" x 2-1/2"	0 to 1-1/2"	50	7	965
GSI-10	120"	1/4" x 18" x 60"	Cat. 1 & 2	1/2" x 6"	3/8" x 2-1/2"	0 to 1-1/2"	70	9	1155

Specifications subject to change without notice

## Innovative, Rugged & Labor Saving Attachments

www.rankinequipment.com