THE ORIGINAL SINCE 1992!

HYREACH SLIPPER

Extreme Duty With Industry Leading Reach!



Maximum Cut Between 9" & 12"



Cut Hard to Reach Areas





FEATURES:

- Boom Extends Cutting Surface to 10' 3" and Retracts to 7' 3"
- Control the Cutting, Rotating & Telescoping from Inside the Cab with a Wireless Remote
- 180° Rotation of Clipper Head to Cut Limbs on Both Sides of the Tree
- 664000 Extreme Duty Clipper Head–Our STRONGEST!
- Rectangular Telescoping Boom for Maximum Strength
- Optional PIN Connectors Available





01

THE ORIGINAL SINCE 1992!

HYREACH SLIPPER EXTREME DUTY





664000 Clipper Head

MODEL ED6451



Offset Tractor Mount



Clean Fence Rows



Power Rotate to Trim Limbs

FEATURES:

- Extra Long Upper and Lower Plate Weldments and Supports for Added Strength
- Self-Cleaning Side Spacers to Prevent Buildup of Dirt & Debris That Could Cause Damage
- "Easy-Release" to Prevent Trees & Limbs from Getting Wedged Between Blades
- Fully Plumbed with Hoses, Couplers, Hose Wrap, Solenoid Valve, & Valve Guard
- Cut at Ground Level or Power Rotate Head to Trim Limbs
- Six-Foot Reach Allows High Reach Cutting
- Wireless Remote to Control Rotation



PRECISIONMFG.COM



THE ORIGINAL SINCE 1992!

HYREACH CLIPPER CLAMPIC

Control The Fall Of Trees & Protect Your Equipment!

Backstop

Hardened Clamp Blades Welded Clamp Cylinder

> Greased Pivot Points

> > Before



Hold & Cut Limbs



Hold & Cut Trees at Ground Level



Neatly Stack Trees & Limbs

CLAMPit can also be ADDED

Center Load Support

to an existing XD or ED series HyReach Clipper

Load limit for CLAMPit is 200 lbs Visit www.PRECISIONMFG.com/CLAMPit for our log size and weight chart.



After

9

SOLVING TREE & BRUSH PROBLEMS SINCE 1992!



Finally, A Tree Shear For Smaller Equipment!

MC7551 - Adds Auxilary Hydraulics to Tractor



Three Brace Supports

Telescopes 6', 7', 8'

7" Cut Capacity

180° Rotation



Optional Sprayer is Available See our accessories for details at



Counter Weight Recomended



Skid Steers & Tractors with Auxilary Hydraulics



MC7551 - Extended 8 ft

• Weight 632 lbs

•

Fully Plumbed with Couplers

Minimum 1200 lb Lift Required

Universal Quick Attach Brackets

2500 PSI Hydraulic Pressure Required