

**TECHNICAL SPECIFICATIONS
AND STANDARD EQUIPMENT**

- maximum horsepower: 250 HP (183 KW)
- PTO: 2-speed gearbox for 1000 rpm
No. of teeth for models 300-400
25-14 = 323 rpm; 24-15 = 360 rpm
No. of teeth for models 350-450
14-25 = 323 rpm; 15-24 = 360 rpm
- 3-point hitch cat.2
- swinging front hitches



- roller adjustment with hydraulic system
- rear leveling bar, adjustment with threaded bar
- round tine holder to avoid jamming
- tines 100x18x320 mm (working depth, approximately 33 cm)
with low power absorption
- mobile side plates
- drive shaft with automatic safety device
- removable safety devices

MAXI									
	cm	cm	HP / KW	Kg	Kg	Kg	Kg	No.	
300	305	300	140/102	1,320	1,320	1,490	1,350	24	Drive shaft S.10 L=1,053 tractor side 1"3/8 Z=21
350	355	350	160/117	1,450	1,450	1,640	1,480	28	
400	405	400	180/131	1,580	1,580	1,790	1,610	32	
450	455	450	200/146	1,710	1,710	1,940	1,740	36	

MAXI	cage roller		spikes roller		packer roller		spiral roller	
300	500		560		555		470	
350								
400								
450								

OPTIONAL ACCESSORIES:	
2-speed gearbox with rear PTO for 1000 rpm PTO*	
Oil cooling kit*	
Oil cooling kit* (supplied at a later time)	
Rear rollers - see page 209 -	
Roller adjustment by pins	
Stone protector kit	
Counterplate for tine locking (rotor kit)	
Counterplate for tine locking (rotor kit) (supplied at a later time)	
Front track eraser	
Rear hydraulic hitches for seeder	
*NOTE: When the machine is equipped with rear PTO, the oil cooling kit cannot be fitted (and vice versa).	



Stone protector

