

FOLDING POWER HARROWS

MAXI P

HP 180-350

KW 132-255










450 HP -OPTIONAL-



NOTE: Hitch with 4-ram lifting on request

TECHNICAL SPECIFICATIONS AND STANDARD EQUIPMENT

- maximum horsepower: 350 HP (255 KW)
- PTO: 2-speed gearbox for 1000 rpm
No. of teeth: 17-22 = 357 rpm; 18-21 = 396 rpm
- 3-point hitch cat.3
- swinging front hitches
- rollers with adjustment using pins linked to the leveling bar
- rear leveling bar adjustment with threaded bar
- tines 100x18x320 mm: working depth, approximately 33 cm
- tines with low power absorption
- mobile side plates
- side drive shafts with automatic safety device
- central drive shaft
- rear lights for road transport
- removable safety devices
- cooler for side gearboxes with reservoir
- side lifting with double ram (mod.600-700)*

MAXI P									
	cm	cm	HP / KW	Kg	Kg	Kg	Kg	No.	
500	500	246	180/132	2,520	2,650	3,000	2,680	40	Central drive shaft S.10 L=952 tractor side 1"3/4 Z=20
600*	600	246	200/146	2,750	2,920	3,470	2,950	48	
700*	700	246	220/160	2,980	3,190	3,900	3,220	56	

MAXI P	cage rollers		spikes rollers		packer rollers		spiral rollers	
500	500		560		555		470	
600*								
700*								

OPTIONAL ACCESSORIES:

Oil cooling kit for central gearbox	
Stone protector kit for rotor	
Counterplate for tine locking (rotor kit)	
Counterplate for tine locking (rotor kit) (supplied at a later time)	
Front track eraser	
Gearbox 450 HP with oil cooling for central and side gearbox	
Floating system kit	
Central track eraser tool	
Rear rollers - see page 209	
Hydraulic kit for roller adjustment	

BED FORMER VERSION

