

FIXED POWER HARROW

MINIGO









HP 30-80

KW 22-59



TECHNICAL SPECIFICATIONS AND STANDARD EQUIPMENT

- maximum horsepower: 80 HP (59 KW)
- PTO: 1-Speed for 540 rpm: 319 rpm
- 3-point hitch cat.1
- set-up for rippers
- roller with pin adjustment
- tines 90x10x260 mm: working depth about 26 cm
- drive shaft with shear bolt
- welded safety devices

MINIGO								
	cm	cm	HP / KW	Kg	Kg	Kg	No.	
100	107	100	30/22	325	355	385	8	Drive shaft S.6 L=1,020 tractor side 1"3/8 Z=6
125	131	125	35/26	370	400	445	10	
150	156	150	40/29	415	445	505	12	
175	180	175	45/33	460	490	535	14	

MINIGO	cage roller		spikes roller		packer roller	
100	385		500		420	
125						
150						
175						

OPTIONAL ACCESSORIES:

4-speed gearbox for 540 rpm PTO
mod.100

No. of teeth 16-19 = 269 rpm • 17-18 = 301 rpm
No. of teeth 18-17 = 338 rpm • 19-16 = 379 rpm

mod.125-150-175

No. of teeth 19-16 = 269 rpm • 18-17 = 301 rpm
No. of teeth 17-18 = 338 rpm • 16-19 = 379 rpm

Rear rollers

Counterplate kit

Stone protector kit for rotor

Stone protector kit + counterplates for round rotor

Stone protector kit + rotor counterplate (supplied at a later time)

Front ripper (wing type) (supplied only with reinforced frame)

Front ripper (chisel type) (supplied only with reinforced frame)

Front track eraser (supplied only with reinforced frame)

Rear leveling bar

Mobile side plates kit

Movable side plates kit (supplied at a later time)

Drive shaft (inner/outer tubes) with clutch safety device