

MOUNTED SIDE DELIVERY RAKE

RP2 / RP4 / RP5 / RP6 / RP8 / RP10 / RP12



Rake with very sturdy equipment.
Independent and interchangeable wheels mounted on roller bearings. Left and right SPREADING – TURNING and RAKING action, also suitable for limited place.

Suspension springs.

Hubs with taper roller bearings and sealed dust cover on all units.

Reversible arms for spreading -turning and raking

Specifications	RP2	RP4	RP5	RP6	RP8	RP10	RP12
Weight	145 Lbs 66 kg	396 Lbs 180 Kg	440 Lbs 200 Kg	551 Lbs 250 Kg	1013 Lbs 460 Kg	1145 Lbs 520 Kg	1366 Lbs 620 Kg
Working Width Raking	79 in 2.00 m	103 in 2,60 m	138 in 3,50 m	162 in 4,1 m	217 in 5,50 m	295 in 7.50 m	342 in 8.7 m
Working Width Spreading and Turning	79 in 2.00 m	114 in 2,90 m	154 in 3,90 m	173 in 4,4 m	240 in 6,10 m	342 in 8,70 m	394 in 10 m

Designs, materials and/or specifications are subject to change without notice and without liability thereof.



Organization with certified Management System ISO 9001