



TECHNICAL SPECIFICATIONS AND STANDARD EQUIPMENT

- maximum horsepower: 130 HP (96 KW)
- PTO: 1-Speed for 540 rpm: 324 rpm
- swinging front hitches
- 3-point hitch cat.2
- roller with pin adjustment
- tines 90x12x285 mm: working depth about 28 cm
- mobile side plates
- drive shaft with shear bolt
- removable safety devices

RANGER									
	cm	cm	HP / KW	Kg	Kg	Kg	Kg	No.	
225	230	225	75/55	730	740	830	750	18	Drive shaft S.8 L=893 tractor side 1"3/8 Z=6
250	255	250	80/59	770	790	880	800	20	
300	305	300	85/62	860	880	980	890	24	

RANGER	cage roller		spikes roller		packer roller		spiral roller	
225	385				420			
250			500				470	
300	440		560		470			

OPTIONAL ACCESSORIES:

4-speed gearbox for 540 rpm PTO (for Ranger 1V)
 model 300 No. of teeth 16-19 = 273 rpm • 17-18 = 306 rpm
 No. of teeth 18-17 = 343 rpm • 19-16 = 385 rpm
 model 225-250 No. of teeth 19-16 = 273 rpm • 18-17 = 306 rpm
 No. of teeth 17-18 = 343 rpm • 16-19 = 385 rpm

2-speed gearbox for 1000 rpm PTO (only for Ranger 4-speed)

4-speed gearbox for 540 rpm PTO (only for Ranger 4-speed)
 model 225-250 No. of teeth 22-13 = 355 rpm • 21-14 = 400 rpm
 model 300 No. of teeth 13-22 = 355 rpm • 14-21 = 400 rpm

4-speed gearbox for 540 rpm PTO and rear PTO (only for Ranger 4V)

2-speed gearbox for 1,000 rpm PTO and rear PTO (only for Ranger 4V)

OPTIONAL ACCESSORIES:					
Rear rollers - see page 209 -					-
Rear leveling bar H=120 mm with threaded bar adjustment					
model 225		model 250		model 300	
Rear leveling bar H=160 mm with threaded bar adjustment					
model 225		model 250		model 300	
Tines counterplate kit, round rotor (supplied at a later time)					
Stone protector kit for rotor					
Counterplate kit + rotor stone protector					
Tines counterplate kit with stone protectors, round rotor (supplied at a later time)					
Hydraulic kit for roller adjustment					
Hydraulic kit for roller adjustment (supplied at a later time)					
Front track eraser					
Set-up for front fitting (models 250-300)					
Front fitting kit complete with front wheels (models 250-300) (only for models with front fitting set-up)					
Rear hydraulic hitches for seeder					
Front leveling bar					
	model 250			model 300	
Drive shaft (inner/outer tubes) with clutch safety device					
Drive shaft with automatic safety device					

Also available in shift
version
(see following page)

