












NOTE: Hydraulic adjustment for rear rollers is supplied on request

TECHNICAL SPECIFICATIONS AND STANDARD EQUIPMENT

- maximum horsepower: 210 HP (154 KW)
- PTO: 1-Speed for 1,000 rpm: 392 rpm
- 3-point hitch cat.2
- swinging front hitches
- roller adjustment with pins
- rear leveling bar adjustment with threaded bar
- tines 90x12x285 mm: working depth, approximately 28 cm
- mobile side plates
- side drive shafts with shear bolt
- central drive shaft
- rear lights for road transport
- removable safety devices

RANGER P									
	cm	cm	HP / KW	Kg	Kg	Kg	Kg	No.	
400	400	227	130/96	1,660	1,684	1,796	1,700	32	Central drive shaft S.8 L=761 tractor side 1"3/8 Z=21
450	450	227	145/107	1,795	1,822	1,948	1,840	36	
500	500	227	160/118	1,930	1,960	2,100	1,980	40	

RANGER P	cage rollers		spikes rollers		packer rollers		spiral rollers	
400	440		560		470		470	
450								
500								

OPTIONAL ACCESSORIES:

4-speed side gearboxes for 1000 rpm No. of teeth 16-19 = 330 rpm; 17-18 = 370 rpm; 18-17 = 415 rpm; 19-16 = 465 rpm	
3-point hitch category 3	
3-point hitch category 3 (supplied at a later time)	
Rear rollers - see page 209	
Tines counterplate kit, round rotor (supplied at a later time)	
Stone protector kit for rotor	
Tines counterplate kit with stone protectors, round rotor	
Tines counterplate kit with stone protectors, round rotor (supplied at a later time)	
Floating system kit	
Central track eraser tool	
Front track eraser	
Hydraulic kit for roller adjustment	