EN

# ISN
















## **FIXED VERSION**



Parking stand

40 mm



#### **TECHNICAL DATA**

They allow the adjustment

of the working height.

#### **Reducer speed:**



Counterblade

chamber

system in cutting




#### **Models and Features:**

	<b>⊚</b> HP	$\underset{\text{i} \leftarrow \text{i}}{ \underset{\text{i} \leftarrow \text{i}}{ }} \underset{\text{(in)}}{\text{mm}}$	mm (in)	mm (in)	kg (lbs)	nr.	nr. nr.	nr.	cat.
TSN 95	45 ▶ 80	950 (37")	1130 (44")	300(12")	250 (551)	24	6	4	1-2
TSN 110	45 ▶ 80	1100 (43")	1250 (49")	300(12")	290 (640)	32	8	4	1-2
TSN 125	45 ▶ 80	1250 (49")	1400 (56")	300 (12")	320 (705)	32	8	4	1-2
TSN 140	45 ▶ 80	1400 (55")	1550 (61")	300 (12")	396 (872)	40	10	4	1-2
TSN 155	45 ▶ 80	1550 (61")	1700 (67")	300 (12")	422 (930)	40	10	4	1-2
TSN 170	45 ▶ 80	1700 (67")	1850 (73")	300 (12")	450 (1000)	48	12	4	1-2
TSN 185	45 ▶ 80	1850 (73")	2000 (79")	300 (12")	465 (1025)	48	12	4	1-2
TSN 200	45 ▶ 80	2000 (79")	2150 (85")	300 (12")	500 (1102)	56	14	4	1-2


## **MOVABLE VERSION**

Medium-heavy multi-purpose movable shredder for tractors from 45 to 80 HP with widths from 95 to 200 cm and can be equipped with knives, toothed or smooth hammers.



#### **TECHNICAL DATA**

#### **Reducer speed:**



#### **Models and Features:**


	<b>®</b> MP	nm (in)	mm (in)	mm (in)	kg (lbs)	nr.	nr. nr.	nr.	cat.
TSN 125	45 ▶ 80	1250 (49")	1400 (56")	300 (12")	320 (705)	32	8	4	1-2
TSN 140	45 ▶ 80	1400 (55")	1550 (61")	300 (12")	396 (872)	40	10	4	1-2
TSN 155	45 ▶ 80	1550 (61")	1700 (67")	300 (12")	422 (930)	40	10	4	1-2
TSN 170	45 ▶ 80	1700 (67")	1850 (73")	300 (12")	450 (1000)	48	12	4	1-2
TSN 185	45 ▶ 80	1850 (73")	2000 (79")	300 (12")	465 (1025)	48	12	4	1-2
TSN 200	45 ▶ 80	2000 (79")	2150 (85")	300 (12")	500 (1102)	56	s4	4	1-2



Universal shaft (Eurocardan) size 6
































Medium-heavy multi-purpose movable shredder for tractors from 45 to 80 HP with widths from 95 to 200 cm and can be equipped with knives, toothed or smooth hammers. Furthermore, thanks to its bevelled side it allows it to work flush with the body avoiding problems of friction or impact.

The new bevelled side allows you to work flush to the body, avoiding common problems caused by friction or impact



#### **TECHNICAL DATA**

#### **Reducer speed:**





#### **Models and Features:**

	<b>® ®</b> HP	mm (in)	mm (in)	mm (in)	∆ kg (lbs)	nr.	nrnr.	nr.	cat.
TSN-Q 140	45 ▶ 80	1400 (55")	1550 (61")	300 (12")	410 (904)	40	10	4	1-2
TSN-Q 155	45 ▶ 80	1550 (61")	1700 (67")	300 (12")	430 (948)	40	10	4	1-2
TSN-Q 170	45 ▶ 80	1700 (67")	1850 (73")	300 (12")	450 (1000)	48	12	4	1-2
TSN-Q 185	45 ▶ 80	1850 (73")	2000 (79")	300 (12")	470 (1036)	48	12	4	1-2
TSN-Q 200	45 ▶ 80	2000 (79")	2150 (85")	300 (12")	500 (1102)	56	4	4	1-2

### **ROTOR AND TOOL VERSIONS TSN**

performance machine, as its rotation allows the tools used and the diameter. to shred grass or pruning residues. The most important

The perfect operation of the shredder largely depends characteristics of the rotor (excluding the width as bulk on the rotor, an essential component of a high- and weight) are undoubtedly the thickness of the steel





For grass, shrubs, lawn maintenance; vines, mediumsized pruning; pruning of woody residue from vineyards and olive groves.

**HELICOIDAL SMOOTH** 





#### **HELICOIDAL KNIVES**

For grass, shrubs, lawn maintenance; vine shoots, straw, stalks.







#### **HELICOIDAL TOOTHED HAMMERS**

For grass, vine shoots, medium-sized pruning.



# **ROTOR AND TOOL VERSIONS TSN-Q**





#### **HELICOIDAL KNIVES**

For grass, shrubs, lawn maintenance: vine shoots. straw, stalks.







#### **HELICOIDAL TOOTHED HAMMERS**

For grass, vine shoots, medium-sized pruning.



## **ACCESSORIES**



#### Mower disc with spring return

Disc without a sensor for direct impact with the plant for return.

Available only for the TSN version



#### Mower disc with hydraulic sensor

Disc that, thanks to the sensor, retracts in advance, preventing the direct impact of the disc on the plant.

Available only for the TSN version



#### Side skids

They allow the adjustment of the working height.



# Rubber swivelling wheel to replace roller

Ideal for stony soils and does not compact the ground like a roller.

# The experience that cultivates the future of your land

SICMA S.p.a. is an Italian company and a leader in the professional agricultural machinery sector. We design and create cutting-edge solutions for you, the farmer of tomorrow. Innovation and passion at your service.





#### Sicma SpA

Contrada Cerreto, 39 66010 Miglianico (CH) Tel. +39 0871 95841

info@sicma.it - www.sicma.it







