



## BELT RAKE

### FEATURES:

- Forms a light and airy windrow (not braided)
- Turns any type of hay, even at high speed
- Cat. 1, 3-point hitch
- Requires minimum 20HP tractor to operate

MODELS	DESCRIPTION	WEIGHT
GSE-220	Belt Rake, 87" Working Width	694

## FINGERWHEEL RAKES

### FEATURES:

- For turning, windrowing, spreading and raking
- Sturdy construction
- Cat. 1, 3-point hitch
- 55" diameter wheels, 40 teeth per wheel
- Wheels mounted on roller bearings



MODELS	DESCRIPTION	WEIGHT
RP-2	2 Wheel, 3-point Windrow Turner	145
RP-3	3 Wheel, 3-point Windrow Turner	210
RP-4	4 Wheel, 3-point Side Delivery Rake	366



## QUICK RAKES

### FEATURES:

- Rake folds to transport when lifted
- Choice of 8, 10, or 12 wheels
- Adjustable wheel pressure
- Follows uneven terrain
- Includes hydraulic cylinders and hoses

MODELS	DESCRIPTION	WEIGHT
QR-8	8 Wheel Quick Rake, 18' working width	1500
QR-10	10 Wheel Quick Rake, 21' working width	1630
QR-12	12 Wheel Quick Rake, 24'-6" working width	1830
230-371	Center Wheel Kit, QR Series	
230-735	Hydraulic Angle Kit, QR-8 and QR-10	
230-736	Hydraulic Angle Kit, QR-12	





### QUICK RAKE X

**FEATURES:**

- Rake folds to transport when lifted
- Choice of 12 or 14 wheels
- Adjustable wheel pressure
- Tandem axle wheels and tires
- Follows uneven terrain
- Includes hydraulic cylinders and hoses

MODELS	DESCRIPTION	WEIGHT
QRX-12	12 Wheel Quick Rake, 25'-7" working width, 60" wheels	2670
QRX-14	14 Wheel Quick Rake, 28' working width, 60" wheels	2955
250-747	Center Wheel Kit, QRX Series	

## ROTARY WINDROWERS

### SINGLE ROTOR DRIVEN

**FEATURES:**

- Working width 10' & 13'-9"
- Suited for any type of forage on any terrain
- Forms consistent windrows without twisting
- Removable tine arms for transport
- Operates at 350 - 450 RPM
- Tandem axle wheels and tires



MODELS	DESCRIPTION	WEIGHT
320-8	Rotary Windrower, 10' working width, pull type	991
420-11	Rotary Windrower, 13'-9" working width, pull type	1233

## HEAVY-DUTY V-RAKES



### PRO 17 RAKE

**FEATURES:**

- Maximum working width: 29'
- Electro-hydraulic valves operate all functions
- Double tine rubber mounted teeth
- Adjustable independent wheel pressure
- Walking beam tires and wheels
- Rake wheel diameter: 60"
- Transport width: 12'-3", length 28'-3"

MODEL	DESCRIPTION	WEIGHT
PRO-17	High speed heavy duty V-Rake, 29' working width	5550
230-805	Pro-19 Conversion Kit, 32' working width	