



Snow Blades

Designed for skid steers and tractor front loaders, heavy duty snow blades remove snow easily from driveways, parking lots or other large areas. Available in 5, 6, 7½ and 9 foot widths. 7½' and 9' blades feature 5 degree lateral oscillation allowing these wider blades to easily follow the ground contour. SBS models utilize the "Universal" skid steer mounting system. SBFL models offer interfacing brackets for most tractor front loaders. SBC models easily install on compact tractors by clamping onto the bucket for fast snow removal.

- Ideal for residential or commercial snow removal.
- Two trip springs for controlled break over in snow.
- Reinforced 21" or 27" high 10-gauge moldboards provide long service life.
- 3/8" x 6" reversible cutting edge of 1044 steel.
- Optional Ultra-Rubber cutting edge is available for all sizes.
- Step-through design allows for easy access to skid steer seat.
- Quick hook up on skid steers or front loaders equipped with "Universal" mounting plate.
- Select models integrate either the Euro/Global or John Deere 400/500 series mounting for easier hook up.
- Two bucket clamp-on models are offered for compact tractors.
- SBFL models can be paired with optional brackets for most tractor loaders.
- Blade angles right or left.
- Adjustable skid shoes of AR-400 steel are ½" thick and rotate for long life.



See the Snow Blade in action on YouTube!
(<https://www.youtube.com/watch?v=pJ3oWGWtYa4>)



Adjustable skid shoes are standard



27-Series Snow Blade 7-1/2' and 9' Specifications For Skid Steer and Tractors w/ Loader 40 – 95 HP, Max.

	SBFL-27108A	SBS-27108A	SBG-27108A	SBJD-27108A	SBFL-2790A	SBS-2790A	SBG-2790A	SBJD-2790A
Overall Width (in/cm)	108 / 274	108 / 274	108 / 274	108 / 274	90 / 229	90 / 229	90 / 229	90 / 229
Overall Height (in/cm)	27 / 69	27 / 69	27 / 69	27 / 69	27 / 69	27 / 69	27 / 69	27 / 69
Moldboard Thickness	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge
Cutting Edge (in/cm) 3/8 x 6 / 9.525 x 152.4	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
5° Lateral Oscillation	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Extension Trip Springs	2	2	2	2	2	2	2	2
Manual Angle Positions	N/A	N/A	N/A	N/A	5	5	5	5
Width @ Full Angle	96 / 244	96 / 244	96 / 244	96 / 244	80 / 203	80 / 203	80 / 203	80 / 203
Tractor Loader Mount	*Brackets Req.	N/A	Euro / Global	400 / 500 JD	*Brackets Req.	N/A	Euro / Global	400 / 500 JD
Skid Steer Mount	N/A	Universal	N/A	N/A	N/A	Universal	N/A	N/A
Adjustable Skid Shoes	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Horse Power Rating	50-95 HP	50-95 HP	50-95 HP	50-95 HP	40-80 HP	40-80 HP	40-80 HP	40-80 HP
Weight (lbs/kg)	748 / 339	735 / 333	717 / 325	765 / 347	660 / 299	646 / 293	630 / 286	675 / 306
Hydraulic Angle Kit	Standard	Standard	Standard	Standard	Optional	Optional	Optional	Optional
Crossover Ref. Valve	Standard	Standard	Standard	Standard	Optional	Optional	Optional	Optional
Optional Top Deflector	360230	360230	360230	360230	360227	360227	360227	360227
Optional Sight Indicator	360235	360235	360235	360235	360235	360235	360235	360235
Optional Rubber Cutting Edge Kit	358059	358059	358059	358059	358058	358058	358058	358058
Product No.	360075	360070	360078	360275	360085	360080	360090	360270

*Optional interfacing quick attach brackets available for most popular models.



WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer are properly counterbalanced. Damage to equipment or personal injury could occur.



21-Series Snow Blade 5' and 6' Specifications
 For Skid Steer and Tractors w/ Loader 25 -45 HP, Max.
 Clamp-on Models for Tractors up to 35 HP, Max.

	SBFL-2172	SBS-2172	SBC-2172	SBJD-2172	SBFL-2160	SBS-2160	SBC-2160	SBJD-2160
Overall Width (in/cm)	72 / 183	72 / 183	72 / 183	72 / 183	60 / 152	60 / 152	60 / 152	60 / 152
Overall Height (in/cm)	21 / 53	21 / 53	21 / 53	21 / 53	21 / 53	21 / 53	21 / 53	21 / 53
Moldboard Thickness	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge
Cutting Edge (in/cm) 3/8 x 6 / 9.525 x 152.4	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Extension Trip Springs	2	2	2	2	2	2	2	2
Manual Angle Positions	5	5	5	5	5	5	5	5
Width @ Full Angle	62 / 157	62 / 157	62 / 157	62 / 157	52 / 132	52 / 132	52 / 132	52 / 132
Tractor Loader Mount	*Brackets Req.	N/A	Clamp-On	200 / 400 JD	*Brackets Req.	N/A	Clamp-On	200 / 400 JD
Skid Steer Mount	N/A	Universal	N/A	N/A	N/A	Universal	N/A	N/A
Adjustable Skid Shoes	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Horse Power Rating	<45 HP	<45 HP	<35 HP	<45 HP	<45 HP	<45 HP	<35 HP	<45 HP
Weight (lbs/kg)	360 / 163	353 / 160	335 / 152	373 / 169	335 / 152	325 / 147	305 / 138	345 / 156
Hydraulic Angle Kit	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Crossover Ref. Valve	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Optional Top Deflector	360223	360223	360223	360223	360220	360220	360220	360223
Optional Sight Indicator	360235	360235	360235	360235	360235	360235	360235	360235
Optional Rubber Cutting Edge Kit	358056	358056	358056	358056	358054	358054	358054	358054
Product No.	360160	360130	360290	360225	360140	360100	360280	360250

*Optional interfacing quick attach brackets available for most popular models.



WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer are properly counterbalanced. Damage to equipment or personal injury could occur.



Mini Skid Steer Snow Blades

Designed for Mini Skid Steers / Compact Tool Carriers, this 50" snow blade is ideal for clearing sidewalks, eliminating hand shoveling. Incorporating many of the features of our larger snow blades, this blade consistently delivers the performance you demand.

- Two trip springs for controlled breakover in snow
- 3/8" x 6" reversible cutting edge
- Standard Skid Shoes of abrasive resistance steel

Mini Skid Steer Snow Blade Specifications

	SBMS-50	SBMS-50 B/G
Overall Width (in/cm)	50 / 127	50 / 1270
Overall Height (in/cm)	21 / 53.34	21 / 53.34
Moldboard Thickness	10-gauge	10-gauge
Cutting Edge (in/cm)	3/8 x 6 / 0.9525 x 15.24	3/8 x 6 / 0.9525 x 15.24
Mount	Universal Mini Skid	Bobcat MT / Gehl*
Weight (lbs/kg)	280 / 127	280 / 127
Product No.	360245	360260

* Note: Also for Bobcat S-70 & Gehl 1640 small cab type units.

Hydraulic Concrete Mixers

WorkSaver's Skid Steer Mixer, model SS-590 has direct hydraulic drive of the gearbox which eliminates chain and sprocket maintenance resulting in more up-time on the jobsite. Large 11-cubic ft. drum allows the operator to mix, transport and place 5-cubic ft. of concrete. It's efficient design offers the contractor a cost savings over chain driven models.

- All welded steel drum construction with internal paddles for uniform mixing and clean dumping.
- Compact, trouble free, long life design with few moving parts.
- Direct hydraulic drive of the gearbox eliminates chain & sprocket maintenance.
- Flow control valve allows easy control of mixer speed.
- All welded frame with store onboard parking stands for easy storage of the mixer when not in use.



Concrete Mixer Specifications

	SS-590
Capacity	Five (5) cu/ft (1 Bag Mix)
Drum Opening (in/cm)	20 / 51
Overall Drum Length (in/cm)	32 / 81
Drum Construction	Welded Steel
Drive System	Hydraulic Direct Thru Gearbox
Hydraulic Requirements	Minimum 8 GPM
Hitch Requirements	N/A
Drive Ratio	3.18:1
Flow Control Valve	Standard
Connect Under Pressure Couplers	Standard
Parking Stands	Standard
Shipping Weight (lbs/kg)	395 / 180
Product No.	780950



WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer are properly counterbalanced. Damage to equipment or personal injury could occur.