



36-Series Snow Pusher



36-Series Snow Pusher
w/Optional Pull-Back Kit



See the 36-Series Snow Pusher in action on YouTube!
(<https://www.youtube.com/watch?v=oFZSJv9OjI4>)

Snow Pushers 36-Series

Engineered for Skid Steer loaders and Utility tractors from 50-90 hp. (depending on model) these 36-Series Snow Pushers consistently deliver the high performance today's operators demand. All models feature an adjustable & reversible 1.5" x 8" Ultra-Rubber cutting edge, 4-inch wide reversible skid shoes of AR-400 steel and 7-gauge moldboard.

- Two (2) 4-inch industrial "C" channels provide solid support.
- Pusher side plates are 36" high (without skid shoe) and 36" deep.
- Ultra-Rubber cutting edge of SBR (Styrene Butadiene Rubber) with a durometer of 65 and a 2500# tensile strength provides high performance and durability.
- Models for Skid Steer Loaders.
- Models for John Deere 400/500 (JD hook & pin) quick change attachment carrier.
- Models for Global / Euro tool carrier.
- Blank Back models to accept weld-on mounting brackets.
- Clamp-on bucket mount models.



Clamp-on Bucket Mount 36-Series Snow Pusher
w/Optional Pull-Back Kit

36-Series Snow Pusher Specifications for Skid Steer and Tractor Loaders

	SPS-3696R	SPJD-3696R	SPG-3696R	SPS-36120R	SPJD-36120R	SPG-36120R
Overall Width (in/cm)	104.5 / 265	104.5 / 265	104.5 / 265	128.5 / 326	128.5 / 326	128.5 / 326
Overall Height (in/cm)	37.37 / 95	37.37 / 95	37.37 / 95	37.37 / 95	37.37 / 95	37.37 / 95
Overall Depth (in/cm)	37.75 / 96	37.75 / 96	37.75 / 96	37.75 / 96	37.75 / 96	37.75 / 96
Moldboard Thickness	7-gauge	7-gauge	7-gauge	7-gauge	7-gauge	7-gauge
Endplate Thickness (in/cm)	5/16 / 0.795	5/16 / 0.795	5/16 / 0.795	5/16 / 0.795	5/16 / 0.795	5/16 / 0.795
Reinforced Endplates	Yes	Yes	Yes	Yes	Yes	Yes
Rubber Cutting Edge	Yes	Yes	Yes	Yes	Yes	Yes
Adjustable/ Reversible Skid Shoes	Std.	Std.	Std.	Std.	Std.	Std.
Horsepower Rating	50-90 HP	50-90 HP	50-90 HP	50-125 HP	50-125 HP	50-125 HP
Weight (lbs./kg)	815 / 370	780 / 354	810 / 367	905 / 408	870 / 395	900 / 408
Mounting	Skid Steer	JD 400/500	Euro/Global	Skid Steer	JD 400/500	Euro/Global
Product No.	358060	358070	358080	358090	358100	358110
Optional Pull-Back Kit	358120	358120	358120	358125	358125	358125

36-Series Snow Pusher Specifications for Skid Steer and Tractor Loaders

	SPC-3696R	SPC-36120R	SPB-3696R	SPB-36120R
Overall Width (in/cm)	104.5 / 265	128.5 / 326	104.5 / 265	128.5 / 326
Overall Height (in/cm)	37.37 / 95	37.37 / 95	37.37 / 95	37.37 / 95
Overall Depth (in/cm)	37.75 / 96	37.75 / 96	37.75 / 96	37.75 / 96
Moldboard Thickness	7-gauge	7-gauge	7-gauge	7-gauge
Endplate Thickness (in/cm)	5/16 / 0.795	5/16 / 0.795	5/16 / 0.795	5/16 / 0.795
Reinforced Endplates	Yes	Yes	Yes	Yes
Rubber Cutting Edge	Yes	Yes	Yes	Yes
Adjustable/ Reversible Skid Shoes	Std.	Std.	Std.	Std.
Horsepower Rating	50-90 HP	50-125 HP	50-90 HP	50-125 HP
Weight (lbs./kg.)	845 / 383	935 / 424	775 / 351	865 / 392
Mounting	Bucket / Chain-on	Bucket / Chain-on	Mgt. Brt. Available*	Mgt. Brt. Available*
Product No.	358110	358150	358130	358135
Optional Pull-Back Kit	358120	358125	358120	358125

*Optional weld-on Quick Attach brackets available for most popular loaders.



Snow Pushers 24-Series

Engineered to fit compact tractors equipped with a loader. The 24-Series Snow Pusher is job matched to the tractor for maximum performance.

- Replaceable 1" x 6" reversible Ultra-Rubber cutting edge is standard on "R" models
- Replaceable 3/8" x 6" reversible steel cutting edge is standard on "M" models
- Models to fit loaders with "Universal" skid steer attaching system.
- Models to fit John Deere 200/300/400 series loaders with quick attach system.
- All models feature adjustable & reversible skid shoes of AR-400 steel.



24-Series Snow Pusher Specifications For Tractors up to 50 HP, Max., "Universal" Skid Steer Attach

	SPS-2460R	SPS-2460M	SPS-2472R	SPS-2472M	SPS-2484R	SPS-2484M
Overall Width (in/cm)	66.5 / 169	66.5 / 169	78.5 / 199.4	78.5 / 199.4	90.5 / 230	90.5 / 230
Overall Height (in/cm)	25.6 / 65	25.6 / 65	25.6 / 65	25.6 / 65	25.6 / 65	25.6 / 65
Overall Depth (in/cm)	26 / 66	26 / 66	26 / 66	26 / 66	26 / 66	26 / 66
Moldboard Thickness	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge
End Plate Thickness (in/cm)	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635
Reinforced Endplates	Yes	Yes	Yes	Yes	Yes	Yes
Rubber Cutting Edge	Yes	No	Yes	No	Yes	No
Steel Cutting Edge	No	Yes	No	Yes	No	Yes
Skid Shoes of AR-400	Std.	Std.	Std.	Std.	Std.	Std.
Horsepower Rating	20-30 HP	20-30 HP	25-40 HP	25-40 HP	30-50 HP	30-50 HP
Operating Weight of Power Unit	3,500 lbs. Max.	3,500 lbs. Max.	3,500 lbs. Max.	3,500 lbs. Max.	3,500 lbs. Max.	3,500 lbs. Max.
Weight (lbs/kg)	390 / 177	410 / 186	430 / 195	450 / 204	465 / 211	485 / 220
Product No.	358000	358005	358010	358015	358020	358025
Optional Pull-Back Kit	358095	358095	358105	358105	358115	358115
Optional Poly Skid Shoes	358245	358245	358245	358245	358245	358245

24-Series Snow Pusher Specifications For John Deere Tractors up to 50 HP, Max.

John Deere Hook & Pin Quick Attach for 200/300/400, D120, D160, D170, H120, H130, H160, H165, H180

	SPJD-2460R	SPJD-2460M	SPJD-2472R	SPJD-2472M	SPJD-2484R	SPJD-2484M
Overall Width (in/cm)	66.5 / 169	66.5 / 169	78.5 / 199.4	78.5 / 199.4	90.5 / 230	90.5 / 230
Overall Height (in/cm)	25.6 / 65	25.6 / 65	25.6 / 65	25.6 / 65	25.6 / 65	25.6 / 65
Overall Depth (in/cm)	26 / 66	26 / 66	26 / 66	26 / 66	26 / 66	26 / 66
Moldboard Thickness	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge
End Plate Thickness (in/cm)	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635
Reinforced Endplates	Yes	Yes	Yes	Yes	Yes	Yes
Rubber Cutting Edge	Yes	No	Yes	No	Yes	No
Steel Cutting Edge	No	Yes	No	Yes	No	Yes
Skid Shoes of AR-400	Std.	Std.	Std.	Std.	Std.	Std.
Horsepower Rating	20-30 HP	20-30 HP	25-40 HP	25-40 HP	30-50 HP	30-50 HP
Operating Weight of Power Unit	3,500 lbs. Max.	3,500 lbs. Max.	3,500 lbs. Max.	3,500 lbs. Max.	3,500 lbs. Max.	3,500 lbs. Max.
Weight (lbs/kg)	379 / 172	399 / 181	415 / 188	435 / 197	450 / 204	470 / 213
Product No.	358030	358035	358040	358045	358050	358055
Optional Pull-Back Kit	358095	358095	358105	358105	358115	358115
Optional Poly Skid Shoes	358245	358245	358245	358245	358245	358245



WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer are properly counterbalanced. Damage to equipment or personal injury could occur.

Snow Pushers 20-Series

Performance matched to fit Sub-Compact tractors, the 20-Series Snow Pushers are sized to the tractor for maximum performance. Models are available with the “universal” skid steer attach method, which is used on most sub-compact loaders today. Also available are models to fit John Deere 200/300/D120/H120/H130 with hook & pin quick attach.



- Models designed for Sub-Compact tractors up to 32 HP.
- End plates with gentle slope design.
- Adjustable skid shoes of AR-400 material.
- Available in widths of 4' or 5' with either an ultra-rubber edge or alloy steel cutting edge.
- CNC formed 11-gauge moldboard with formed 10-gauge back brace for strength and durability.
- Optional Pull-Back kit available for all models.

20-Series Snow Pusher Specifications For Sub-Compact Tractors up to 32 HP, Max.
“Universal” Skid Steer Attach

	SPS-2048R	SPS-2048M	SPS-2060R	SPS-2060M
Overall Width (in/cm)	52 / 132	52 / 132	64 / 163	64 / 163
Overall Height (in/cm)	21.5 / 55	21.5 / 55	21.5 / 55	21.5 / 55
Overall Depth (in/cm)	21 / 53	21 / 53	21 / 53	21 / 53
Moldboard Thickness	11-gauge	11-gauge	11-gauge	11-gauge
End Plate Thickness	7-gauge	7-gauge	7-gauge	7-gauge
Inside Angle Bracing	Yes	Yes	Yes	Yes
Rubber Cutting Edge	Yes (1" x 4")	No	Yes (1" x 4")	No
Alloy Steel Cutting Edge	No	Yes (3/8" x 4")	No	Yes (3/8" x 4")
Skid Shoes of AR-400	Yes	Yes	Yes	Yes
Horsepower Rating	Up to 32 HP	Up to 32 HP	Up to 32 HP	Up to 32 HP
Operating Weight of Power Unit	1,800 lbs. Max.	1,800 lbs. Max.	1,800 lbs. Max.	1,800 lbs. Max.
Weight (lbs/kg)	146 / 66	163 / 74	159 / 72	180 / 82
Product No.	358160	358165	358170	358175
Optional Rubber Edged Pull-Back Kit	358200	358200	358205	358205
Optional Metal Edged Pull-Back Kit	358230	358230	358235	358235
Optional Poly Skid Shoes	358240	358240	358240	358240

20-Series Snow Pusher Specifications For John Deere Sub-Compact Tractors up to 32 HP, Max.
John Deere Hook & Pin Quick Attach for 200/300, D120, H120, H130

	SPJD-2048R	SPJD-2048M	SPJD-2060R	SPJD-2060M
Overall Width (in/cm)	52 / 132	52 / 132	64 / 163	64 / 163
Overall Height (in/cm)	21.5 / 55	21.5 / 55	21.5 / 55	21.5 / 55
Overall Depth (in/cm)	21 / 53	21 / 53	21 / 53	21 / 53
Moldboard Thickness	11-gauge	11-gauge	11-gauge	11-gauge
End Plate Thickness	7-gauge	7-gauge	7-gauge	7-gauge
Inside Angle Bracing	Yes	Yes	Yes	Yes
Rubber Cutting Edge	Yes (1" x 4")	No	Yes (1" x 4")	No
Alloy Steel Cutting Edge	No	Yes (3/8" x 4")	No	Yes (3/8" x 4")
Skid Shoes of AR-400	Yes	Yes	Yes	Yes
Horsepower Rating	Up to 32 HP	Up to 32 HP	Up to 32 HP	Up to 32 HP
Operating Weight of Power Unit	1,800 lbs. Max.	1,800 lbs. Max.	1,800 lbs. Max.	1,800 lbs. Max.
Weight (lbs/kg)	131 / 59	148 / 67	145 / 66	166 / 75
Product No.	358180	358185	358190	358195
Optional Rubber Edged Pull-Back Kit	358200	358200	358205	358205
Optional Metal Edged Pull-Back Kit	358230	358230	358235	358235
Optional Poly Skid Shoes	358240	358240	358240	358240



WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer are properly counterbalanced. Damage to equipment or personal injury could occur.

Choose **WORKSAVER** For All Your Land Management