

WRAPPER

WR1600 / WR1800 / WR2100 / WR3100 / WR5100



WRAPPER

WR1600 - BALE WRAPPER WITH SATELLITE



Strong, particularly suitable for small spaces and on sloping field

- 3 point hitch version for front and rear linkage
- Handy and safe, it works at few cm from the ground
- Particularly suitable for small or uncomfortable spaces
- Good results also in steep slope grounds
- It could wrap bales from 120 to 160 cm diameter and till 1200 kg weight

Constant synchronization between the bale and satellite film stretcher rotation.

Film overlapping is uniform at any speed. Regulation of film height (750 or 500) is made by the replacing of the transmission pinion. The model "1600B" is equipped with hydraulic brakes, which help to avoid uncontrolled satellite film stretcher rotation in hilly areas.



Film stretcher 75-50 cm



Aluminium film-stretcher dispenser



Hydraulic cutting mechanism



Electronic rev counter

WRAPPER

WR1800 - 3 POINT HITCH BALE WRAPPER

Easy to use and low power demand

- 3 point hitch version suitable for static use
- Suitable for use directly in the storage place
- Bale loading with another equipment
- Bale discharge by hydraulic control

A lot of features of this static version are common to more professional machines:

- Control devices by flexible cables
- Easy use and low power required
- The belts guarantee the wrapping up of imperfect or small diameter bales



Film stretcher 75-50 cm



Aluminium film-stretcher dispenser



Electronic rev counter



Automatic reset of the cutting system



WRAPPER

WR2100 - TRAILED BALE WRAPPER WITH FORK LOADING



Light and maneuverable, suitable for all types of bales.

- Trailed or carried version with central loading arm for rear loading
- Light and handy, is suitable for all bales from 120 to 160 cm diameter
- Loading and discharge by fork with hydraulic control from the tractor
- Possibility of wrapping also during bale transport
- Standard with half-automatic centring

The advantages of the central loading arm are:

- Possibility to load bales up to 1200 kg, also misshapen
- Suitable for use on slopes, with discharge of the bale without risks of rolling
- Loading of the bale on slopes, the cradle smoothly and discharges the bales, one near the other, without risks of film damage



Film stretcher 75-50 cm



Aluminium film-stretcher dispenser



Automatic reset of the cutting system



Central loading fork



Adjustable draw bar



Electronic rev counter

WRAPPER

WR3100 - TRAILED BALE WRAPPER WITH SIDE ARM

Trailed version with side fork for professional use

The will of Mascar to offer a big range of models to its customers is completed with this version, suggested to farms with having high productive requirement and heavy bales.

- Trailed version with side loading fork
- High performance in large areas
- Low ground pressure and high stability
- Half-automatic centring
- Possibility to load bales till 900 kg without the use of ballast
- Direct discharge of the bale, without the use of the platform
- “Optional” discharge vertical bale



Film stretcher 75-50 cm



Aluminium film-stretcher dispenser

The main features of this model are:


- Frame with mobile wheel in two positions:
 - Inner for transport
 - Outer for work
- Cradle mounted on fifth wheel diameter 500 mm, as warranty of long lasting
- Half-automatic centring of the cradle for fast and efficient use
- Bale discharge close the soil and without use of the platform:
 - Adjustable draw bar
 - Automatic functions for ease of operation



Automatic reset of the cutting system



Adjustable loading fork



2 reel supports



Adjustable draw bar



Electronic rev counter

WRAPPER

WR5100 - TRAILED BALE WRAPPER WITH SIDE ARM



For farms with large production requirements and heavy bales weight

- Trailed version with side loading fork, for professional use in big farms
- Strong frame with possibility to carry two bales
- Bale discharge with rear damper
- Strong platform for the vertical bale discharge



Film stretcher 75-50 cm



Aluminium film-stretcher dispenser



Automatic reset of the cutting system



Adjustable draw bar



Adjustable loading fork



2 reel supports



Rear platform to unload bale or vertical overturning



Electronic rev counter

Specifications	WR1600	WR1800	WR2100	WR3100	WR5100
Length	2,48m	2,51m	3,26m	4,32m	4,82m
Transport Width	1,58m	1,70m	1,74m	2,44m	2,42m
Height	2,38m	2,10m	2,26m	2,40m	2,88m
Weight	820 kg	770 Kg	860 kg	900 kg	1640 kg
Bale dimensions	Diameter min 1,2m - max 1,6m	Diameter min 1,2m - max 1,6m	Diameter min 1,2m - max 1,6m	Diameter min 1,2m - max 1,6m	Diameter min 1,2m - max 1,6m
Tyre Size	/	/	20-10 6PR	10.0/80-12	13-55/16
Max. load round bales	1200 Kg	1200 Kg	1200 Kg	900 Kg	1300 kg
Power Required	70 HP	30 HP	30 HP	30 HP	50/70 HP

Designs, materials and/or specifications are subject to change without notice and without liability thereof.

Your partner in farming



Organization with certified Management System ISO 9001