



FIXED ROTARY TILLERS



TIGER 280DD DOUBLE DRIVE SERIES • HP 180-280

TECHNICAL SPECIFICATIONS:

- 10" working depth
- Double drive side transmission
- Gear driven 340/375 RPM
- Central gearbox oil cooler
- Side gearbox oil coolers
- 1-3/4-20 1000 RPM PTO
- Central loosening tine
- 3-Point hitch, Cat. 2 & 3
- Hydraulic rear roller adjustment
- Threaded bar tailgate adjustment
- C shaped blades (10mm)
- Rotor with double welded flanges
- Drive shafts with slip clutches
- Equipped with rear cage roller

SPECIFICATIONS

MODELS	WORKING WIDTH	OVERALL WIDTH	HP REQUIRED	BLADES	WEIGHT
T280DD-400	12'-8"	13'-5"	180	90	4410
T280DD-450	14'-4"	15'-1"	200	102	4675
T280DD-500	16'-1"	16'-8"	220	114	4940



TIGER 280DD SERIES



TIGER 250 SERIES



TIGER 190 SERIES



FIXED ROTARY TILLERS

TIGER 250 SERIES • HP 140-250



TECHNICAL SPECIFICATIONS:

- 10" working depth
- 3 speed gearbox for 540/1000 RPM PTO
- Oil Cooler with radiator
- 3-point hitch, Cat. 2 & 3
- Swinging lower linkages
- Threaded bar tailgate adjustment
- C shaped blades (10mm)
- Rotor with double welded flanges
- Drive shaft with slip clutch
- Equipped with rear cage roller

SPECIFICATIONS

MODELS	WORKING WIDTH	OVERALL WIDTH	HP REQUIRED	BLADES	WEIGHT
T250-255	8'-5"	9'-2"	140	60	2600
T250-305	10'-1"	10'-8"	160	72	2866
T250-355	11'-8"	12'-5"	180	84	3130

TIGER 190 SERIES • HP 100-190



TECHNICAL SPECIFICATIONS:

- 10" working depth
- 2 speed gearbox for 1000 RPM PTO
- Oil Cooler with radiator
- Drive shaft with slip clutch
- 3-point hitch, Cat. 2 & 3
- Swinging lower linkages
- Threaded bar tailgate adjustment
- C shaped blades (10mm)
- Rotor with double welded flanges
- Equipped with rear cage roller
- Removable safety devices

SPECIFICATIONS

MODELS	WORKING WIDTH	OVERALL WIDTH	HP REQUIRED	BLADES	WEIGHT
T190-255	8'-5"	9'-2"	120	60	2470
T190-280	9'-3"	10'	140	66	2600
T190-305	10'-1"	10'-8"	160	72	2735



Phone (800) 426-2009 / (509) 453-8271 • Fax: (509) 457-2456

www.rankinequipment.com