



# FOLDING ROTARY TILLERS



## SUPER TIGER 360P SERIES • HP 200-360

### TECHNICAL SPECIFICATIONS:

- 11" working depth
- Double drive side transmission
- Gear driven 340/375 RPM
- Central gearbox oil cooler
- Side gearbox oil coolers
- 1-3/4-20 1000 RPM PTO
- 3-point hitch, Cat. 3
- Swinging lower linkages
- Central loosening tine
- Hydraulic tailgate adjustment
- Hydraulic rear roller adjustment
- C shaped blades (10mm)
- Rotor with double welded flanges
- Drive shafts with cam clutches
- Equipped with rear cage roller

### SPECIFICATIONS

MODELS	WORKING WIDTH	TRANSPORT WIDTH	HP REQUIRED	BLADES	WEIGHT
T360P-500	16'-1"	8'-6"	200	114	7275
T360P-550	17'-7"	8'-6"	220	1126	7605
T360P-600	19'-4"	8'-6"	240	138	7936



**SUPER TIGER 360P**



**TIGER 280P**



**PIONEER 260P**



# FOLDING ROTARY TILLERS

## TIGER 280P SERIES • HP 180-280



### TECHNICAL SPECIFICATIONS:

- 10" working depth
- 2 speed gearbox for 1000 RPM PTO
- Central gearbox oil cooler
- Side gearbox oil coolers
- 3-point hitch, Cat. 3
- Swinging lower linkages
- Central loosening tine
- Threaded bar tailgate adjustment
- Hydraulic rear roller adjustment
- C shaped blades (10mm)
- Rotor with double welded flanges
- Drive shafts with cam clutches
- Equipped with rear cage roller

### SPECIFICATIONS

MODELS	WORKING WIDTH	TRANSPORT WIDTH	HP REQUIRED	BLADES	WEIGHT
T280P-450	14'-4"	8'-6"	180	102	6768
T280P-500	16'-1"	8'-6"	200	114	7098
T280P-550	17'-7"	8'-6"	220	126	7429

## PIONEER 260P SERIES • HP 110-190



### TECHNICAL SPECIFICATIONS:

- 10" working depth
- 2 speed gearbox for 1000 RPM PTO
- Central gearbox oil cooler models 450/500
- 3-point hitch, Cat. 3
- Swinging lower linkages
- Central loosening tine
- Threaded bar tailgate adjustment
- Hydraulic rear roller adjustment
- C shaped blades (10mm)
- Rotor with double welded flanges
- Drive shafts with cam clutches
- Equipped with rear cage roller
- Removable safety devices

### SPECIFICATIONS

MODELS	WORKING WIDTH	TRANSPORT WIDTH	HP REQUIRED	BLADES	WEIGHT
P260P-400	12'-8"	8'-3"	150	90	5114
P260P-450	14'-4"	8'-3"	170	102	5555
P260P-500	16'-1"	8'-3"	200	114	5995



Phone (800) 426-2009 / (509) 453-8271 • Fax: (509) 457-2456

[www.rankinequipment.com](http://www.rankinequipment.com)