

# E10 direct

 2,5-6 tons [5,5k-13k lbs]

 max. 10 cm [4 inch]

## Powerful Mulcher for Your Compact Excavator minimal weight, maximum rigidity and full performance

The E10 direct offers the perfect balance of load capacity and low weight for mini excavators from 2.5 to 6 tons. This keeps your excavator safe, agile, and precise even at maximum reach.

The hydraulic motor in this model is coupled directly to the rotor, ensuring smooth operation without belts. The gauges of the CUT-CONTROL system limit the cutting depth. All these features make the attachment ideal for mini excavators, delivering fine mulching results at rapid pace.

### Standard version and specifications

- > Mulches brush and wood up to 10 cm [4"] Ø

---

- > Excavator category 2.5-6 tons [5,500-13,000 lbs]

---

- > Chassis made of high tensile and wear-resistant steel AR400

---

- > Universal attachment interface

---

- > Direct transmission gear motor 11 cm<sup>3</sup> PLUG & PLAY with DRAINLESS system

---

- > Rear protection with chains

---

- > Support skids with replaceable wear plates

---

- > CUT CONTROL rotor system with MINI BLADE V-LOCK hammers

---

- > BOLTED ROTOR SHAFT

---

- > Replaceable tempered COUNTER CUTTERS

---

### Optional configuration and accessories

- > CUT CONTROL system with MINI DUO V-LOCK hammers

---


- > Individual interface plate for an excavator arm

---

- > 190° rotation plate

---




 YouTube [www.youtube.com/seppimulcher](http://www.youtube.com/seppimulcher)

### Specifications · E10 direct

	cm ["]	60 cm [24"]	85 cm [33"]
Working width	cm ["]	60 cm [24"]	85 cm [33"]
Overall width	cm ["]	100 cm [39"]	125 cm [49"]
Depth	cm ["]	54 cm [21"]	54 cm [21"]
Height	cm ["]	51 cm [20"]	51 cm [20"]
Weight · base value w/o options	kg [lbs]	190 kg [420 lbs]	220 kg [490 lbs]
MINI BLADE V-LOCK · standard	qty	12	18
MINI DUO V-LOCK	qty	12	18

### Tools





## High-performance hydraulic drive

The **E10 direct** for excavators with a flow rate of 25-60 l/min is driven by a gear motor and is equipped with the **DRAINLESS** system as standard. It therefore only requires a supply line and a free return line – ideal for small excavators without a leak oil line or for companies with several mini excavators in their fleet.

HYDRAULIC DRIVE	E10 direct
Pressure	100-230 bar [1,450-3,350 psi]
Return line pressure	max. 5 bar [72 psi]
Required hydraulic flow	25-60 l/min [6-16 gpm]
<b>Required hydraulic lines:</b>	
For excavators up to max. 5 tons [11klbs]: The maximum pressure in the return should not exceed 5bar[72psi]. If a pressure of 5 bar cannot be maintained, a drainage line is required.	
Optional rotation plate: 2 (right/left)	

### AR400

Robust chassis made of wear-resistant steel

